

Features + Specifications



IP54-600439

Intended Use:

- Building interior/exterior
- **Ø4"** Ceiling recessed mount
- Approved for IC and AT application
- Wet location listed

Construction:

- Trim made from extruded/machined aluminium
- Body and heat sink made from extruded aluminium
- Recessed housing made from sheet metal

Finish (LED Light Module):



- Powder coat paint
- Polished chrome plated

Optical System:

- High power LED 50000+ hrs rated
- 3000K or 5000K CCT with 80+ CRI
- Precision made optical lens
- Standard **30°** symmetrical light distribution
- Semi-Specular Alzak cone for glare control
- Bottom frosted lens with gasket for wet location use

Electrical System:

- Electronic driver
- Dimmable driver available
- RoHS compliant
- Short circuit and overheat protected
- Housing approved for feed thru application



Product Code Information

IP54 - 600439 -	LAC	- TRIM -	LAMP	- VOLT. -	DRIVER
Lensed Alzak Cone	W=White B=Black A=Aluminum C=Chrome		9W3K=315 lm, 3000K 9W5K=450 lm, 5000K	120=120V 277*=277V 347*=347V	S=Standard D1*=120V dimming D10*=0-10V dimming

Note: * Consult factory for availability and application restrictions.

Project Name:		Fixture Type:	
QTY:	Product Code:		

(use with recessed housing number IP00-600040)