

Project:	Type:	QTY:
Product Code:		

Product Code

IP54 - 208289

COLOR

- ☐ B = Black
☐ CC = Custom Color

SIZE - LED DATA

- ☐ 9W3K = 3000K, 760lm
☐ 9W4K = 4000K, 790lm
☐ 12W3K = 3000K, 980lm
☐ 12W4K = 4000K, 1010lm

- ☐ 15W3K = 3000K, 1200lm
☐ 15W4K = 4000K, 1290lm
☐ 18W3K = 3000K, 1500lm
☐ 18W4K = 4000K, 1605lm

VOLTAGE

- ☐ 120 = 120V
☐ 120D10=120V 0-10 control
☐ *347 = 347V

OPTION

- ☐ SCEC = Surface Conduit Entry Canopy

* 347V, size S2 18W only
 Requires SCEC option

Features + Specifications

Intended Use:

- Building interior
- Building exterior
- Wet location listed

Construction:

- Die-cast aluminum construction
- Hi impact tempered glass lens with silicone gasket
- Full cut-off optics and dark sky friendly, compact and efficient
- Aluminum mounting plate mounts to smooth flat wall surfaces
- Close cell gasket for wall mounting in wet location
- Mounts over 4" flush octagon boxes
- 2 sizes available, approx. S1= 5x5x5 cube & S2= 6x6x6 cube dimensions

Finish:

- Sand textured powder coat paint with UV additive
- Color in Black, (white and Aluminum available with MOQ)
- Custom Color selected from RAL paint chart or Prismatic color chart

Optical System:

- Luminus Gen III COB light module with 90CRI, 3000K & 4000K CCT
- COB direct mount to fixture die-cast aluminum body for excellent heat management
- Check Luminus web portal for their latest LM80 and TM21 technical data
- Flood downlight optics (60°) with clear tempered glass lens
- Size S1 in 9W (760lm) & 12W (980lm) system watt
- Size S2 in 15W (1200lm) & 18W (1500lm) system watt



IP54-208289


Electrical System

- Constant current drive technology
- High efficiency, low THD, RoHS compliant
- Overheat with short circuit protection
- 120 = 120V non-dimming & 120D10 = 120V 0-10 dimming driver available
- 347 = 347V, please consult factory, size S2 18W only, requires use of SCEC


Mounting:

- Recommended 8ft max mounting height
- Mounts over 4" flush octagon boxes
- Optional surface conduit entry canopy

Dimensions:



Options:



	A	B	C	X	Z
S1	4.75"	4.75"	4.75"	4.25"	1.8"
S2	6"	6"	6"	5.5"	1.8"



Right reserved for material and spec modification without prior notice

Datocode 20220401