

Project:	Type:	QTY:
Product Code:		

Product Code:

IP54 - 208900

COLOR

- ☐ B = Black
☐ W = White
☐ A = Aluminum

INTENSITY

- ☐ 8W ☐ 927
☐ 12W ☐ 930
☐ 18W ☐ 940

DIRECTION

- ☐ D = Downlight
☐ UD = Up/Down
☐ UDW = Up/Down Wallwash
☐ DW = Downlight Washwall

VOLTAGE

- ☐ 120 = 120V
☐ 120D10 = 120V, 0-10 dim

Features + Specifications

Intended Use:

- Building interior/exterior
- Wall mounting
- Wet location listed

Construction:

- Die-cast aluminum construction
- Designed for full cut off down light (D/DW)
- Up/down (UD) consists of 2 light modules
- Up/down wallwash (UDW) consists of 1 light module
- Clear tempered glass lens
- Aluminum mounting plate with closed cells foam gasket
- Extruded silicone gasketing
- Stainless steel fasteners

Finish:

- Sand textured powder coat paint
- Color in Black, White and Aluminum
- Contact factory for Custom Color

Optical System:

- Multiple mid-power LED linear light module
- LEDs on all aluminum PCB for effective heat management
- Samsung or Osram 3528 LEDs, 90CRI, L70@50000+hrs
- Available CCT 2700K, 3000K & 4000K
- Check Samsung/Osram web portal for their latest LM80 and TM21 technical data
- UD optics use 2 modules (one per direction)

APERTURE LUMENS

	2700K (927)	3000K (930)	4000K (940)
8W	752	800	845
12W	1125	1200	1260
18W	1690	1800	1910



IP54-208200

Electrical System:

- Constant current driver technology
- High efficiency, low THD, RoHS compliant
- Overheat and short circuit protection
- 120V line dimmable with most wall box type dimmers, 120V 0-10 dimming also available

Mounting:

- Mounts directly over octagon box

Dimensions:

